



QUICKSTAIN LACQUER WIPING STAIN 1LS-1XXX

Features

- 11 Pre-Mixed Popular Colors
- Tint Base for Custom Colors
- Ready to Use Formulations
- Uniform Penetration
- Helps Against Blotching
- Superior Grain Definition
- Resists Fading and Bleeding
- Fast Drying for Lacquers

General Description

Lenmar® QuickStain Lacquer Wiping Stains have been uniquely designed for the professional woodworker in the Furniture & Cabinet Industry and are formulated strictly for use in shop applications only. The major benefits of this stain line include: 11 of the most popular pre-mixed stain colors, a natural / clear tint base for custom tinting with 844 colorants (or another approved system), capability to intermix different colors to create new stains, ease of application for uniform penetration, superior grain definition, and resistance to bleeding and fading. Do not apply multiple coats of stain, remove all excess stain, and allow to thoroughly dry before top coating.

Recommended For

Kitchen Cabinets, Furniture, Window and Door Trim, Baseboards and Molding, Interior Doors and Handrails.

Limitations

- Not for use on Floors.

Product Information

Product Information																																																													
<p>Colors — Standard: 1LS-1203 New England Walnut 1LS-1204 Dark Mahogany 1LS-1206 Spice Brown 1LS-1207 Golden Oak 1LS-1208 Fruitwood 1LS-1209 Special Walnut 1LS-1210 Spanish Oak 1LS-1211 Salem Maple 1LS-1212 Ebony 1LS-1213 White 1LS-1217 Dark Walnut</p>	<table border="1"> <thead> <tr> <th colspan="2">Technical Data◇</th> <th>White</th> </tr> </thead> <tbody> <tr> <td>Vehicle Type</td> <td></td> <td>Proprietary</td> </tr> <tr> <td>Pigment Type</td> <td></td> <td>N/A</td> </tr> <tr> <td>Weight Solids</td> <td></td> <td>15%</td> </tr> <tr> <td>Volume Solids</td> <td></td> <td>10%</td> </tr> <tr> <td>Coverage per Gallon at 1 mil DFT</td> <td></td> <td>N/A</td> </tr> <tr> <td>Recommended Film Thickness</td> <td>– Wet – Dry</td> <td>N/A N/A</td> </tr> <tr> <td>Dry Time @ 75 °F (23.8 °C) @ 50% RH</td> <td>– Spray & Wipe – Spray No Wipe</td> <td>10 – 15 Minutes 20 – 30 Minutes</td> </tr> <tr> <td colspan="3">High humidity and cool temperatures will result in longer dry and recoat times.</td> </tr> <tr> <td>Dries By</td> <td></td> <td>Evaporation</td> </tr> <tr> <td>Viscosity</td> <td></td> <td>18 – 22 Seconds (#2 Zahn)</td> </tr> <tr> <td>Flash Point</td> <td></td> <td>64 °F (17.8 °C)</td> </tr> <tr> <td>Gloss / Sheen</td> <td></td> <td>N/A</td> </tr> <tr> <td>Surface Temperature at Application</td> <td>– Min. – Max.</td> <td>68 °F 90 °F</td> </tr> <tr> <td>Thin With</td> <td></td> <td>Do Not Thin</td> </tr> <tr> <td>Clean Up Thinner</td> <td></td> <td>1A-406 or 1A-519 Lacquer Thinner</td> </tr> <tr> <td>Weight Per Gallon</td> <td></td> <td>6.49 – 9.77 lbs</td> </tr> <tr> <td>Storage Temperature</td> <td>– Min. – Max.</td> <td>50 °F 90 °F</td> </tr> <tr> <td colspan="3" style="text-align: center;">Volatile Organic Compounds (VOC)</td> </tr> <tr> <td></td> <td>819 Grams/Liter</td> <td>6.16 Lbs./Gallon</td> </tr> </tbody> </table>	Technical Data◇		White	Vehicle Type		Proprietary	Pigment Type		N/A	Weight Solids		15%	Volume Solids		10%	Coverage per Gallon at 1 mil DFT		N/A	Recommended Film Thickness	– Wet – Dry	N/A N/A	Dry Time @ 75 °F (23.8 °C) @ 50% RH	– Spray & Wipe – Spray No Wipe	10 – 15 Minutes 20 – 30 Minutes	High humidity and cool temperatures will result in longer dry and recoat times.			Dries By		Evaporation	Viscosity		18 – 22 Seconds (#2 Zahn)	Flash Point		64 °F (17.8 °C)	Gloss / Sheen		N/A	Surface Temperature at Application	– Min. – Max.	68 °F 90 °F	Thin With		Do Not Thin	Clean Up Thinner		1A-406 or 1A-519 Lacquer Thinner	Weight Per Gallon		6.49 – 9.77 lbs	Storage Temperature	– Min. – Max.	50 °F 90 °F	Volatile Organic Compounds (VOC)				819 Grams/Liter	6.16 Lbs./Gallon
Technical Data◇		White																																																											
Vehicle Type		Proprietary																																																											
Pigment Type		N/A																																																											
Weight Solids		15%																																																											
Volume Solids		10%																																																											
Coverage per Gallon at 1 mil DFT		N/A																																																											
Recommended Film Thickness	– Wet – Dry	N/A N/A																																																											
Dry Time @ 75 °F (23.8 °C) @ 50% RH	– Spray & Wipe – Spray No Wipe	10 – 15 Minutes 20 – 30 Minutes																																																											
High humidity and cool temperatures will result in longer dry and recoat times.																																																													
Dries By		Evaporation																																																											
Viscosity		18 – 22 Seconds (#2 Zahn)																																																											
Flash Point		64 °F (17.8 °C)																																																											
Gloss / Sheen		N/A																																																											
Surface Temperature at Application	– Min. – Max.	68 °F 90 °F																																																											
Thin With		Do Not Thin																																																											
Clean Up Thinner		1A-406 or 1A-519 Lacquer Thinner																																																											
Weight Per Gallon		6.49 – 9.77 lbs																																																											
Storage Temperature	– Min. – Max.	50 °F 90 °F																																																											
Volatile Organic Compounds (VOC)																																																													
	819 Grams/Liter	6.16 Lbs./Gallon																																																											
<p>— Tint Bases: 1LS-1000, Clear Base may be tinted with up to 12 oz. of Industrial Colorants per gallon.</p>																																																													
<p>— Special Colors: Contact your Dealer/Distributor.</p>																																																													
<p>Certification& Qualifications: VOC compliant in federally regulated areas only</p> <p>The products supported by this data sheet contain a maximum of 830 grams per liter VOC (6.93 lbs/gal.) excluding water & exempt solvents. Thinning this material may result in increasing the VOC levels of this product. Refer to your local regulations before thinning.</p>																																																													
<p>Technical Assistance: Available through your local authorized independent Lenmar dealer. For the location of the dealer nearest you, call 1-877-299-3600 or visit www.lenmar-coatings.com</p>																																																													

March, 2024

◇ Reported values are for White.

QuickStain Lacquer Wiping Stain 1LS-1XXX

WARNING! If you scrape sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Application

Over properly prepared interior wood surfaces, apply only one full coat of QuickStain Lacquer Wiping Stain by spray, with a natural bristle brush or with a clean lint-free cloth. Remove all excess stain within 5 minutes after application. When dry (usually 10-15 minutes), continue with sealer and topcoat system in accordance with their Product Data Sheets. For spray-no-wipe applications, reduce a minimum of 2:1 with Lacquer Thinner, n-Butyl Acetate, or Acetone (STAY IN COMPLIANCE WITH LOCAL REGULATIONS) (Two parts thinner to one part stain). Apply in light coats, 1-2 wet mils. Check adhesion before proceeding with this type of application (should be used for light colors only). See characteristics for recommended dry times.

Specifications

Moisture content of wood should be no higher than 9%. Wood must be free of all surface contaminants. Using 120-150 grit sandpaper, sand with the grain and remove all dust. Thoroughly mix stain and intermix multiple containers of same color. Test color before proceeding. Color intensity may vary due to wood species, surface preparation, and method of application. Submerge stain soaked rags in water to avoid spontaneous combustion. Read label and SDS for additional information and warnings.

Clean up

Clean up with 1A-406 or 1A-519 Lacquer Thinner.

Environmental Health & Safety Information

DANGER!

Harmful if swallowed

Causes skin irritation

Causes serious eye irritation

Suspected of causing cancer

Suspected of damaging fertility or the unborn child

May cause respiratory irritation. May cause drowsiness or dizziness

Causes damage to organs through prolonged or repeated exposure

May be fatal if swallowed and enters airways

Highly flammable liquid and vapor

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Wash face, hands and any exposed skin thoroughly after handling. Do not eat, drink or smoke when using this product. Wear eye/face protection. Do not breathe dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ ventilating/ lighting/ equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep cool.

Response: IF exposed or concerned: Get medical advice/attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If skin irritation occurs: Get medical advice/attention. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/ shower. Wash contaminated clothing before reuse. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. Rinse mouth. In case of fire: Use CO₂, dry chemical, or foam for extinction.

Storage: Store locked up. Store in a well-ventilated place. Keep container tightly closed.

Disposal: Dispose of contents/ container to an approved waste disposal plant.



WARNING: Cancer and Reproductive Harm—
www.P65warnings.ca.gov

This document represents hazards of the product referenced above. Refer to the individual Safety Data Sheet for hazards of the specific product you will be using.

**FOR PROFESSIONAL USE ONLY
KEEP OUT OF REACH OF CHILDREN**

**FOR WOOD SUBSTRATES ONLY
FOR INTERIOR USE ONLY**

NOT FOR USE ON FLOORS

This product is intended for Shop or OEM applications. This product may also be compliant under Architectural and Industrial Maintenance regulations in some jurisdictions for field application to stationary structures. Check local regulations.

**READ ALL DIRECTIONS BEFORE USE.
UNDERSTAND ALL DANGERS WITH THIS
PRODUCT PRIOR TO USE.**

**Refer to Safety Data Sheet for
additional health and safety information.**