



Safety Data Sheet

ULAQ NEXT PC WHITE DR



1. Identification

Product identifier	ULAQ NEXT PC WHITE DR
Product code	1M-502
Other means of identification	N.Av.
Recommended use of the chemical and restrictions on use	A protective and/or decorative finish or accompanying product. Not recommended for any other use not detailed on product data sheet or label.
Manufacturer	GEMINI INDUSTRIES, INC. 2300 Holloway Drive El Reno, OK 73036 USA Tel. 1-800-262-5710 Fax 1-405-262-9310 http://www.gemini-coatings.com/
Emergency phone number	24-hour Emergency (spill, leak, exposure or accident) INFOTRAC 800-535-5053 Outside USA, Call Collect 1-352-323-3500 (French & English) HAZMAT Response and SDS Help: EMI 800-510-8510

2. Hazard identification

Summary	Extremely flammable liquid and vapors. Keep away from heat, sparks and open flame. Avoid contact with skin, eyes and clothing. Do not breathe vapors or aerosols. Do not ingest. If ingested consult physician immediately and show this Safety Data Sheet. Wear eye protection, gloves and other protective clothing that are adapted to the task being performed and the risks involved. P.S.: The SIMDUT 2015/GHS hazards classification in this SDS is provided by the manufacturer using a Worst-Case Scenario.
----------------	--

WHMIS 2015/GHS/OSHA HCS 2012



- Flammable liquids (Category 1)
- Serious eye damage/eye irritation (Category 1)
- Skin sensitizer (Category 1)
- Germ cell mutagenicity (Category 1)
- Carcinogenicity (Category 1)
- Reproductive toxicity (Category 1)
- Specific target organ toxicity, single exposure (Category 3)

DANGER

- H224: Extremely flammable liquid and vapour
- H318: Causes serious eye damage
- H350: May cause cancer
- H340: May cause genetic defects
- H360: May damage fertility or the unborn child
- H317: May cause an allergic skin reaction
- H336: May cause drowsiness or dizziness
- H316: Causes mild skin irritation

P201: Obtain special instructions before use.
P202: Do not handle until all safety precautions have been read and understood.
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P240: Ground and bond container and receiving equipment.
P241: Use explosion-proof electrical equipment.
P242: Use only non-sparking tools.
P243: Take action to prevent static discharges.
P261: Avoid breathing vapours and spray.
P271: Use only outdoors or in a well-ventilated area.
P272: Contaminated work clothing should not be allowed out of the workplace.
P280: Wear protective gloves, protective clothing and eye protection.
P308+P313: IF exposed or concerned: Get medical attention.
P303+P361+P353: IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water and soap or shower.
P363: Wash contaminated clothing before reuse.
P333+P313: If skin irritation or rash occurs: Get medical advice/attention.
P304+P340+P312: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell.
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310: Immediately call a doctor.
P370+P378: In case of fire: Use the National Fire Protection Association Class B extinguisher to extinguish.
P403+P233+P235: Store in a well-ventilated place. Keep container tightly closed. Keep cool.
P405: Store locked up.
P501: Dispose of contents and container to a licensed chemical disposal agency in accordance with local, regional and national regulations.

Other hazards which do not result in classification

Skin corrosion/irritation (Category 3).

3. Composition/information on ingredients

Common name	CAS	Weight % content
Butyl acetate (normal)	123-86-4	10 - 30 %
Titanium dioxide	13463-67-7	10 - 30 %
Ethyl alcohol	64-17-5	10 - 30 %
Nitrocellulose	9004-70-0	5 - 10 %
n-Propanol	71-23-8	5 - 10 %
Urea, polymer with formaldehyde, butylated	68002-19-7	3 - 7 %
Acetone	67-64-1	3 - 7 %
Isopropyl alcohol	67-63-0	3 - 7 %
Isobutyl isobutyrate	97-85-8	1 - 5 %
Kaolin	1332-58-7	1 - 5 %
Bis(2-Ethylhexyl) adipate	103-23-1	1 - 5 %
n-Propyl acetate	109-60-4	0.5 - 1.5 %
Naphtha (petroleum), hydrotreated heavy (C6-C13)	64742-48-9	0.1 - 1 %

Note: The manufacturer withholds the actual concentration range of the ingredients as a trade secret.

4. First-aid measures

Inhalation	Move person to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen by trained personnel. If a problem develops or persists, seek medical attention.
Skin contact	Wash skin with warm water and mild soap. Remove contaminated clothing and wash before reuse. If a problem develops or persists, seek medical attention.
Eye contact	IMMEDIATELY! Flush with water for at least 15 minutes. Remove contact lenses if easy to do. Hold eyelids apart to rinse properly. Seek medical attention immediately.
Ingestion	DO NOT induce vomiting, unless recommended by medical personnel. Never give anything by mouth if victim is unconscious or convulsing. If victim is conscious wash out mouth with water and give 1-2 glasses of water to drink. Seek medical attention or contact a Poison Centre immediately.
Other	No information available.
Symptoms	May cause severe eye irritation or eye damage. May cause redness, dryness, rash and slight skin irritation. May cause an allergic reaction of the skin. May cause headache, drowsiness or dizziness.
Notes to the physician	Treat symptomatically. If gastric lavage is performed, suggest endotracheal and/or esophageal control. Danger from lung aspiration must be weighed against toxicity when considering emptying the stomach. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

5. Fire-fighting measures

Suitable extinguishing media	Dry chemicals, alcohol resistant foam, carbon dioxide (CO ₂). Do not use a heavy water jet.
Specific hazards arising from the chemical	Extremely flammable liquid and vapors. Vapours are heavier than air and may travel to an ignition source distant from the material handling point. May be ignited by heat, sparks, flame or static electricity. Do not apply to hot surfaces.
Special protective equipment	Firefighters must wear self contained breathing apparatus with full face mask. Firefighting suit may not be efficient against chemicals.
Special protective actions for fire-fighters	Use water spray to cool fire-exposed containers. Water spray can reduce the intensity of the flames. However, the water jets can spread the fire. Prevent run-off from fire control or dilution from entering streams, sewers or drinking water supply.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Do not touch spilled material. Make sure to wear personal protective equipment mentioned in this Safety Data Sheet.
Environmental precautions	Prevent entry into sewers, closed areas and release to the environment. For a large spill, consult the Department of Environment or the relevant authorities.
Methods and materials for containment and cleaning up	Remove sources of ignition. Ventilate the area well. Absorb with inert material (soil, sand, vermiculite) and place in an appropriate waste disposal clearly identified. Use non-sparking and antistatic tools. Dispose via a licensed waste disposal contractor. Finish cleaning the contaminated surface by rinsing with soapy water.

7. Handling and storage

Precautions for safe handling	Keep away from heat, sparks and open flame. Turn off all pilot lights, flames, stoves, heaters, electric motors, welding equipment and other sources of ignition. Use non-sparking and antistatic tools. Use only in well ventilated area. Do not breathe vapors or aerosols. Avoid contact with skin, eyes and clothing. Wear eye protection, gloves and other protective clothing that are adapted to the task being performed and the risks involved. Keep containers tightly closed when not in use. Do not eat, do not drink and do not smoke during use. After use, wash hands with soap and water. Wash contaminated clothing before reuse.
Conditions for safe storage, including any incompatibilities	Storage and handling should follow the NFPA 30 Flammable and/or Combustible Liquids Code and the National Fire Code of Canada (NFCC). Store tightly closed and in properly labelled container in a dry, cool and well ventilated place. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Store away from oxidizing materials and incompatible materials (see section 10). Keep away from direct sunlight and heat.
Storage temperature	5 to 30°C (41 to 86°F)

8. Exposure controls/personal protection

Immediately Dangerous to Life or Health	N-Butyl acetate: 1700 ppm. Titanium dioxide: 5000 mg/m ³ . Ethyl alcohol: 3300 ppm. n-Propanol: 800 ppm. Isopropyl alcohol: 2000 ppm. Acetone: 2500 ppm. n-Propyl acetate: 1700 ppm.			
Ethyl alcohol	STEL		1000 ppm	ACGIH , BC, ON, RSST
Titanium dioxide	TWA (8h)	Total Dust	10 mg/m ³	ACGIH , BC, ON, RSST
Butyl acetate (normal)	STEL		150 ppm	ACGIH , RSST
			200 ppm	ON
	TWA (8h)		20 ppm	BC
			50 ppm	ACGIH , RSST
n-Propanol	STEL		150 ppm	ON
			250 ppm	614 mg/m ³ RSST
	TWA (8h)		100 ppm	ACGIH , BC, ON, RSST
Acetone	STEL		500 ppm	ACGIH , BC, ON
			1000 ppm	2380 mg/m ³ RSST
	TWA (8h)		250 ppm	ACGIH , BC, ON
			500 ppm	1190 mg/m ³ RSST
Isopropyl alcohol	STEL		400 ppm	ACGIH , BC, ON
			500 ppm	1230 mg/m ³ RSST
	TWA (8h)		200 ppm	ACGIH , BC, ON
			400 ppm	983 mg/m ³ RSST
Kaolin	TWA (8h)	Respirable Dust	2 mg/m ³	ACGIH , BC, ON
		Respirable Dust	5 mg/m ³	RSST
n-Propyl acetate	STEL		250 ppm	ACGIH , BC, ON
			250 ppm	1040 mg/m ³ RSST
	TWA (8h)		200 ppm	ACGIH , BC, ON
			200 ppm	835 mg/m ³ RSST
Naphtha (petroleum), hydrotreated heavy (C6-C13)	TWA (8h)	Mist	5 mg/m ³	ACGIH , RSST
			175 ppm	1200 mg/m ³ Other

Appropriate engineering controls	Provide sufficient mechanical ventilation (general or local exhaust) to keep the airborne concentrations of vapours, mists, aerosols or dust below their respective occupational exposure limits.
Individual protection measures	
Eye	In the workplace, wear safety glasses with side shields. If risk of contact with eyes or/and the face wear chemical splash goggles and/or a face shield.
Hands	Wear nitrile or neoprene gloves. Before using, user should confirm impermeability. Discard gloves with tears, pinholes, or signs of wear. Gloves must only be worn on clean hands.
Skin	Personal protective equipment for the body should be selected based on the task being performed and the risks involved. Wear normal work clothing covering arms and legs as required by employer code. If necessary, wear an apron or long-sleeve protective coverall suit.
Respiratory	Respiratory protection is not required for normal use. Where the conditions in the workplace require a respirator, it is necessary to follow a respiratory protection program. Moreover, respiratory protection equipment (RPE) must be selected, fitted, maintained and inspected in accordance with regulations and standard 29 CFR 1910.134 (OSHA), ANSI Z88.2 or CSA Z 94.11 (Canada) and approved by NIOSH/MSHA. In case of insufficient ventilation or in confined or enclosed space and for an assigned protection factor (APF) up to 10 times the exposure limit, wear a half mask respirator with organic vapour cartridges fitted with P100 filters. For an APF until maximum 100 times of exposure limit, wear a full face respirator mask with organic vapour cartridges and P100 filters.
Feet	Wear rubber boots to clean up a spill.

9. Physical and chemical properties

Physical state	Liquid	Flammability	Flammable
Colour	Coloured	Flammability limits	N/Av.
Odour	Solvent	Flash point	0°C (32°F)
Odour threshold	N/Av.	Auto-ignition temperature	170°C (338°F)
pH	N/Av.	Sensibility to electrostatic charges	Yes
Melting point	N/Av.	Sensibility to sparks and/or friction	No
Freezing point	N/Av.	Vapour density	>1 (Air = 1)
Boiling point	34 to 3000°C (93.2 to 5432°F)	Relative density	1.0824 kg/L (Water = 1)
Solubility	Partially soluble in water	Partition coefficient n-octanol/water	N/Av.
Evaporation rate	< Acetate de butyle	Decomposition temperature	N/Av.
Vapour pressure	N/Av.	Viscosity	N/Av.
Percent Wt. Volatile	57.5171%	Molecular mass	N/Av.
VOC (g/L)	572.6454 g/L	% Volume Volatile (VOC)	68.7761%
VOC (lb/gal)	4.7788 lb/gal	% Wt. Volatile (VOC)	53.0219%

10. Stability and reactivity

Reactivity	No information available.
Chemical stability	Stable under recommended storage conditions.
Possibility of hazardous reactions (including polymerizations)	A dangerous reaction will not occur.
Conditions to avoid	Avoid heat, flame and sparks. Avoid static discharges. Avoid contact with incompatible materials.
Incompatible materials	Strong oxidizing agents (e.g. chlorine, fluorine, nitric acid, perchloric acid, peroxides, nitrates, chlorates, chromates, permanganates and perchlorates), strong acids (e.g. hydrochloric acid, sulfuric acid, phosphoric acid), strong bases (e.g. hydroxides, solutions of ammonia, amines, carbonates).
Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

11. Toxicological information

Numerical measures of toxicity	Butyl acetate (normal)			
	Route	Dose	Species	Effect
	Ingestion	10768 mg/kg	Rat	LD50
	Inhalation	>32.5 mg/l/4h	Rat	LC50
	Skin	>17600 mg/kg	Rabbit	LD50
	Ethyl alcohol			
	Ingestion	7060 mg/kg	Rat	LD50
	Inhalation	39 mg/l/4h	Mouse	LC50
	Skin	20000 mg/kg	Rabbit	LD50
	Titanium dioxide			
	Ingestion	>10000 mg/kg	Rat	LD50
	Inhalation	>6.82 mg/l/4h	Rat	LC50
	Skin	>10000 mg/kg	Rabbit	LD50
	n-Propanol			
	Ingestion	1870 mg/kg	Rat	LD50
		5467 mg/kg	Mouse	LD50
	Inhalation	48 mg/l/4h	Mouse	LC50
	Skin	4060 mg/kg	Rabbit	LD50
	Nitrocellulose			
	Ingestion	>5000 mg/kg	Rat	LD50
	Acetone			
	Ingestion	5800 mg/kg	Rat	LD50
	Inhalation	71.4 mg/l/4h	Rat	LC50
	Skin	15800 mg/kg	Rabbit	LD50
	Isopropyl alcohol			
	Ingestion	5045 mg/kg	Rat	LD50
		3600 mg/kg	Mouse	LD50
	Inhalation	66.1 mg/l/4h	Rat	LC50
	Skin	6280 mg/kg	Rat	LD50
	Bis(2-Ethylhexyl) adipate			
	Ingestion	9100 mg/kg	Rat	LD50
	Inhalation	>5.7 mg/l/4h	Rat	LC50
	Skin	17297 mg/kg	Rabbit	LD50
	Isobutyl isobutyrate			
	Ingestion	12800 mg/kg	Rat	LD50
	Inhalation	48.2 mg/l/4h	Rat	LC50
		>5000 ppm/6h	Rat	LC50
	Skin	>8600 mg/kg	Rabbit	LD50
	Kaolin			
	Ingestion	>15900 mg/kg	Rat	LD50
	Skin	>5000 mg/kg	Rat	LD50


	n-Propyl acetate	Ingestion 8700 mg/kg Rat LD50 Inhalation >16.7 mg/l/4h Rat LC50 Skin >17800 mg/kg Rabbit LD50																					
	Naphtha (petroleum), hydrotreated heavy (C6-C13)	Ingestion >10000 mg/kg Rat LD50 Inhalation >8.5 mg/l/4h Rat LC50 Skin >3200 mg/kg Rabbit LD50																					
Likely routes of exposure	Skin, eyes, inhalation, ingestion.																						
Delayed, immediate and chronic effects	Eye contact	May cause severe eye irritation or eye damage. Eye Irritation/Corrosion, Rabbit (OECD TG 405): tests performed with each ingredient (>1%) of this mixture gave not irritating to corrosive results.																					
	Skin contact	May cause redness, dryness, rash and slight skin irritation. Prolonged and repeated contact may cause dry skin, irritation or dermatitis. Skin Irritation/Corrosion, Rabbit (OECD 404) : tests performed with each ingredient (>1%) of this mixture gave not irritating results.																					
	Inhalation	Inhalation of vapours may cause central nervous system depression such as drowsiness, headache, dizziness, vertigo, nausea and fatigue. The severity of symptoms may vary depending on exposure conditions. Prolonged exposure may cause damage to damage to liver, kidneys, lungs and blood forming organs. Many reports with painters have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage.																					
	Ingestion	Ingestion can cause abdominal pain, nausea, cramps, headache, dizziness, diarrhea and vomiting.																					
	Respiratory or skin sensitization	Paints do not all content allergenic ingredients susceptible to cause allergic skin reaction. However, it is reasonable mentioning that people with a history of skin sensitization may be more susceptible to the effects of this product in increasing the risk of allergic contact dermatitis.																					
	IARC/NTP Classification	<table border="1"> <thead> <tr> <th>Common name</th> <th colspan="2">IARC NTP</th> </tr> </thead> <tbody> <tr> <td>Butyl acetate (normal)</td> <td>-</td> <td>-</td> </tr> <tr> <td>Ethyl alcohol</td> <td>-</td> <td>-</td> </tr> <tr> <td>Titanium dioxide</td> <td>2B</td> <td>-</td> </tr> <tr> <td>n-Propanol</td> <td>-</td> <td>-</td> </tr> <tr> <td>Acetone</td> <td>-</td> <td>-</td> </tr> <tr> <td>n-Propyl acetate</td> <td>-</td> <td>-</td> </tr> </tbody> </table> <p>IARC : 1- Carcinogenic; 2A- Probably carcinogenic; 2B- Possibly carcinogenic. NTP : K- Known to be carcinogens; R- Reasonably anticipated to be carcinogens.</p>	Common name	IARC NTP		Butyl acetate (normal)	-	-	Ethyl alcohol	-	-	Titanium dioxide	2B	-	n-Propanol	-	-	Acetone	-	-	n-Propyl acetate	-	-
Common name	IARC NTP																						
Butyl acetate (normal)	-	-																					
Ethyl alcohol	-	-																					
Titanium dioxide	2B	-																					
n-Propanol	-	-																					
Acetone	-	-																					
n-Propyl acetate	-	-																					
	Carcinogenicity	Contains material which can cause cancer. In the absence of specific test data, the classification of naphtha (petroleum), hydrotreated heavy (C6-C13) (CAS no 64742-48-9) should be determined based on the levels of benzene (CAS no 71-43-2). This classification may not apply if it can be shown that the chemical contains less than 0.1 % w/w benzene. Titanium dioxide in dust form can cause cancer (through inhalation) based on animal data. Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint and caulk. The risk of cancer depends on duration and level of exposure.																					
	Mutagenicity	Contains a potential mutagen ingredient. In the absence of specific test data, the classification of naphtha (petroleum), hydrotreated heavy (C6-C13) (CAS no 64742-48-9) should be determined based on the levels of benzene (CAS no 71-43-2). This classification may not apply if it can be shown that the chemical contains less than 0.1 % w/w benzene.																					
	Reproductive toxicity	Major malformations have been reported in infants born of women who had been working with solvent-based paints (oil-based paints) during pregnancy. Therefore, long-term exposure to solvent-based paints that may occur in occupational life can affect a developing baby (American Journal of Industrial Medicine, 1980).																					
	Specific target organ toxicity -	Central nervous system.																					

	single exposure Specific target organ toxicity - repeated exposure
	Liver, kidneys, lungs, blood forming organs, brain, central nervous system.
Interactive effects	No information available for this product.
Other information	The oral and skin acute toxicity estimates (ATE) of the mixture were calculated to be greater than 2000 mg/kg. The acute toxicity estimate (ATE) by inhalation of the mixture was calculated to be greater than 20 mg/L/4h. These values are not classified according to WHMIS 2015 and OSHA HCS 2012.


12. Ecological information

Ecological toxicity	Fish - Pimephales promelas [flow-through]	LC50 18 mg/L; 96 h (CAS no 123-86-4)
	Aquatic Invertebrate - Daphnia magna	EC50 44 mg/L; 48 h (CAS no 123-86-4)
	Fish - Pimephales promelas - Fresh water	LC50 >500 mg/L; 96 h (CAS no 13463-67-7)
	Aquatic Invertebrates - Daphnia pulex	EC50 >100 mg/L; 48 h (CAS no 13463-67-7)
	Fish - Pimephales promelas [flow-through]	LC50 13400 mg/L; 96 h (CAS no 64-17-5)
	Aquatic Invertebrate - Daphnia magna	EC50 9268 mg/L; 48 h (CAS no 64-17-5)
	Algae - Pseudokirchneriella subcapitata	EC50 579 mg/L; 96 h (CAS no 9004-70-0)
	Fish - Pimephales promelas [flow-through]	LC50 480 mg/L; 96 h (CAS no 71-23-8)
	Aquatic Invertebrate - Daphnia magna	EC50 3642 mg/L; 48 h (CAS no 71-23-8)
	Fish - Fathead minnow, Pimephales promelas - fresh water	LC50 9640 mg/L; 96 h (CAS no 67-63-0)
	Aquatic Invertebrate - Crustaceans, Daphnia Magna	EC50 3644 mg/L; 48 h (CAS no 67-63-0)
	Fish - Oncorhynchus mykiss - Rainbow trout	LC50 4740 mg/L; 96 h (CAS no 67-64-1)
	Aquatic Invertebrate - Daphnia magna	EC50 12600-12700 mg/L; 48 h (CAS no 67-64-1)
	Fish - Pimephales promelas - Fresh water	LC50 12.54 mg/L; 96 h (CAS no 97-85-8)
	Aquatic Invertebrate - Daphnia magna	EC50 55.8 mg/L; 96 h (CAS no 97-85-8)
Fish - Lepomis macrochirus [static]	LC50 0.48-0.85 mg/L; 96 h (CAS no 103-23-1)	
Aquatic Invertebrate - Daphnia magna	EC50 >1.6 mg/L; 48 h (CAS no 103-23-1)	
Persistence	Contains an or many ingredients that may be persistent in aquatic environment.	
Degradability	The product is a mixture of which some ingredients are readily biodegradable (> 60% in 28 days) while other ingredients are not readily biodegradable (<60% in 28 days).	
Bioaccumulative potential	The product is a mixture of which some ingredients have a low bioaccumulation potential (Log Kow of <3 and / or BCF <500) while other ingredients have some potential to bioaccumulate (Log Kow of >3 and / or BCF >500).	
Mobility in soil	The product is a mixture of which some ingredients evaporate very easily from the surface of the soil. Moreover, some ingredients have very high mobility in soil, while other ingredients have moderate to low mobility in soil.	
Other adverse effects	This chemical does not deplete the ozone layer.	

13. Disposal considerations

	<p>Important! Prevent waste generation. Use in full. DO NOT dispose residue in sewers, streams or drinking water supply. Paint residues, including lacquers, dyes, shellacs, varnishes, paint solvents and thinners, can be reprocessed where there is a recovery program. Residues and empty containers must be considered as hazardous waste. Dispose via a licensed waste disposal contractor. Observe all federal, state/provincial and municipal regulations. If necessary consult the Department of Environment or the relevant authorities.</p>
--	--

14. Transport information

UN Number	UN 1263
UN Proper Shipping Name	PAINT
Environmental hazards	This material does not contain marine pollutant.
Special precautions for user	Permit required for transportation with proper DANGER placards displayed on vehicle.
TDG - Transportation of Dangerous Goods (Canada & US DOT)	
Transport hazard class(es)	 Class 3
Packing group	II
IMO/IMDG - International Maritime Transport	
Classification	UN 1263. PAINT. Class 3, PG II. Emergency schedules (EmS-No) F-E, S-E
IATA - International Air Transport Association	
Classification	UN 1263. PAINT. Class 3, PG II.
<p>These transportation classifications are provided as a customer service. As the shipper YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. In addition, if a domestic exemption exists, it is the responsibility of the shipper to define the application of it.</p>	

15. Regulatory information

CANADA

Common name	CAS	CEPA	DSL	NDSL	NPRI
Butyl acetate (normal)	123-86-4	X	X		X
Titanium dioxide	13463-67-7	X	X		
Ethyl alcohol	64-17-5	X	X		X
Nitrocellulose	9004-70-0		X		
n-Propanol	71-23-8	X	X		X
Urea, polymer with formaldehyde, butylated	68002-19-7		X		
Acetone	67-64-1		X		
Isopropyl alcohol	67-63-0	X	X		X
Isobutyl isobutyrate	97-85-8		X		
Kaolin	1332-58-7		X		
Bis(2-Ethylhexyl) adipate	103-23-1	X	X		X
n-Propyl acetate	109-60-4	X	X		X

Common name	CAS	CEPA	DSL	NDSL	NPRI
Naphtha (petroleum), hydrotreated heavy (C6-C13)	64742-48-9		X		X

- CEPA: List of Toxic Substances Managed Under Canadian Environmental Protection Act
- DSL: Domestic Substances List Inventory
- NDSL: Non-Domestic Substances List Inventory
- NPRI: National Pollutant Release Inventory Substances

UNITED STATE OF AMERICA

Common name	CAS	TSCA	CER CLA	EPCRA 313	EPCRA 302/304	CAA 112(b) HON	CAA 112(b) HAP	CAA 112(r)	CWA 311	CWA Prio.
Butyl acetate (normal)	123-86-4	X	X						X	
Titanium dioxide	13463-67-7	X								
Ethyl alcohol	64-17-5	X								
Nitrocellulose	9004-70-0	X								
n-Propanol	71-23-8	X								
Urea, polymer with formaldehyde, butylated	68002-19-7	X								
Acetone	67-64-1	X	X			X				
Isopropyl alcohol	67-63-0	X		X						
Isobutyl isobutyrate	97-85-8	X								
Kaolin	1332-58-7	X								
Bis(2-Ethylhexyl) adipate	103-23-1	X								
n-Propyl acetate	109-60-4	X								
Naphtha (petroleum), hydrotreated heavy (C6-C13)	64742-48-9	X								

- TSCA: Toxic Substance Control Act
- CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act list of hazardous substances
- EPCRA 313: Emergency Planning and Community Right-to-Know Act, Section 313 Toxic Chemicals
- EPCRA 302/304: Emergency Planning and Community Right-to-Know Act, Section 302/304 Extremely Hazardous Substances
- CAA 112(b) HON: Clean Air Act - Hazardous Organic National Emission Standard for Hazardous Air Pollutant
- CAA 112(b) HAP: Clean Air Act - Hazardous Air Pollutants lists pollutants
- CAA 112(r): Clean Air Act - Regulated Chemicals for Accidental Release Prevention
- CWA 311: Clean Water Act - List of Hazardous Substances
- CWA Priority: Clean Water Act - Priority Pollutant list

California Proposition 65

Common name	CAS	Cancer	Reproductive and Developmental Toxicity
Titanium dioxide	13463-67-7	X	

Other regulations

HMIS **NFPA**

③ Health	
③ Flammability	
① Reactivity	
ⓧ Protective Equipment	

16. Other information

Date (YYYY-MM-DD)	GEMINI INDUSTRIES, INC. 2023-12-15
Version	01
Other information	<p>- The GHS hazards classification in this SDS is from the original SDS provided by the manufacturer.</p> <p>REFERENCES:</p> <ul style="list-style-type: none">- Haz-Map, Information on Hazardous Chemicals and Occupational Diseases, https://haz-map.com/- Service du répertoire toxicologique de la Commission des normes, de l'équité, de la santé et de la sécurité du travail (CNESST), https://www.cnesst.gouv.qc.ca/en- NIOSH Pocket Guide to Chemical Hazards, Centers for Disease Control and Prevention, NIOSH Publications, 2007, http://www.cdc.gov/niosh/npg/npg.html- The National Center for Biotechnology Information, National Institutes of Health (NIH), U.S. National Library of Medicine, https://pubchem.ncbi.nlm.nih.gov- IPCS INCHEM, Chemical Safety Information from Intergovernmental Organizations, Canadian Centre for Occupational Health and Safety (CCOHS), Copyright International Programme on Chemical Safety (IPCS), http://www.inchem.org- OECD Existing Chemicals Database, Chemicals Screening Information DataSet (SIDS) for High Volume Chemicals, UNEP publications, https://hpcchemicals.oecd.org/UI/Search.aspx <p>ACGIH: American Conference of Governmental Industrial Hygienists AIHA: American Industrial Hygiene Association HMIS: Hazardous Materials Identification System NFPA: National Fire Protection Association OSHA: Occupational Safety and Health Administration (USA) NIOSH: National Institute for Occupational Safety and Health NTP: National Toxicology Program RSST: Règlement sur la santé et la sécurité du travail (Québec) GHS: Globally Harmonized System IARC: International Agency for Research on Cancer IDLH: Immediately Dangerous to Life or Health STEL: Short Term Exposure Limit (15 min) TWA: Time Weighted Averages WHMIS: Workplace Hazardous Materials Information System</p> <p>To the best of our knowledge, the information contained herein is accurate. However, neither Preventis System, nor the above named supplier, nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.</p>